OD-PREN

GOMMA LIGHT PER INIEZIONE LIGHT INJECTION RUBBER



CENTERPLASTICS COMPOUND & ADDITIVES





DATE: MARCH 2011

MATERIAL SAFETY DATA SHEET

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: D-PREN

CHEMICAL NAME: styrene buthadiene blend

CHEMICAL FAMILY: Rubber

PRODUCT DESCRIPTION: Opaque white pellets

CONTACT ADDRESS: Centerplastics Enterprise co. Ltd, Eastern Industrial road, zip: 516127, Shiwan Town, Boluo Area, Huizhou, Guandong, P.R.China

EMERGENCY TELEPHONE NUMBERS: +86 159 896 61 157

NON EMERGENCY TELEPHONE NUMBERS : Office working hours: 9.00 -12.30 - 14.00-18.00 Tel.: +86 752 611 6072/6073 - Fax: +86 752 611 6070

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

COMPOSITION COMMENTS: Does not contain any harmful or hazardous ingredients.

SECTION 3 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT: Particulates may scratch eye surfaces/cause mechanical irritation.

SKIN CONTACT: Negligible hazard at ambient temperatures (-18 to +38 degrees C; 0 to 100 degrees F). Exposure to hot material may cause thermal burns.

INHALATION: Negligible hazard at ambient temperature (-18 to 38 Deg C; 0 to 100 Deg F) Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.

INGESTION: Minimal toxicity.





DATE: MARCH 2011

MATERIAL SAFETY DATA SHEET

SECTION 4 FIRST AID MEASURES

EYE CONTACT: This product is an inert solid. If in eye, remove as one would any foreign object.

Dust in the eyes: Do not rub eye.

HOT PRODUCT: Immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing, as the damaged flesh can be easily torn.

INHALATION: In case of adverse exposure to vapors and/or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

INGESTION: First aid is normally not required.

SECTION 5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Larger fires: Alcohol resistant foam. Water spray, fog or mist. Small fires: Water spray, dry powder or carbon dioxide. Dry chemicals, sand, dolomite etc.

SPECIFIC HAZARDS

Not classified as flammable but will burn. Carbon Monoxide may be evolved if incomplete combustion occurs.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6 ACCIDENTAL RELEASE MEASURES

LAND SPILL

Recover spilled material and place in suitable containers for recycle or disposal.





DATE: MARCH 2011

MATERIAL SAFETY DATA SHEET

SECTION 7 STORAGE AND HANDLING

STORAGE TEMPERATURE, °F: Ambient

LOADING/UNLOADING TEMPERATURE, °F: Ambient

STORAGE/TRANSPORT PRESSURE, mmHg: Atmospheric LOADING/UNLOADING VISCOSITY. cSt: Solid

STORAGE AND HANDLING: Keep container closed. Handle and open containers with care. Store in a cool, well ventilated place. Do NOT handle or store near an open flame, heat or other sources of ignition. Protect material from direct sunlight.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE CONTROLS

Local exhaust ventilation of process equipment may be needed to control particulate exposures.

PERSONAL PROTECTION

Where contact may occur with hot material, wear thermal resistant gloves, arm protection, and a face shield. Where contact is likely with open systems at ambient temperatures (-18 to 38 deg C, 0 to 100 deg F), wear safety glasses with side shields.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

SOLUBILITY IN WATER, wt. % at °F: Insoluble

VISCOSITY OF LIQUID, cSt at °F: Not applicable SP.

GRAV. OF VAPOR, at 1 atm (Air=1): Not Applicable

EVAPORATION RATE, n-Bu Acetate=1: Not applicable

BOILING POINT, °F: Not applicable

SPECIFIC GRAVITY, °F: 0.90 - 1.15

VAPOR PRESSURE, mmHg at °F: Not Available





DATE: MARCH 2011

MATERIAL SAFETY DATA SHEET

FLASH POINT (°C): >200 Unknown.

SECTION 10 STABILITY AND REACTIVITY

STABILITY Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID None known.

HAZARDOUS POLYMERISATION Will not occur

MATERIALS TO AVOID No incompatible groups noted.

SECTION 11 TOXICOLOGICAL INFORMATION

SKIN CONTACT No specific health warnings noted.

EYE CONTACT No specific health warnings noted.

HEALTH WARNINGS No specific health warnings noted.

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY Not regarded as dangerous for the environment.

MOBILITY Not relevant, due to the form of the product.

BIOACCUMULATION The product is not bioaccumulating.

DEGRADABILITY The product is not readily biodegradable.





DATE: MARCH 2011

MATERIAL SAFETY DATA SHEET

ACUTE FISH TOXICITY Not considered toxic to fish.

SECTION 13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

MSDS N° 0281

Incinerate in suitable combustion chamber. or Dispose of on site land-fill area.

SECTION 14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID). No transport warning sign required.

ROAD TRANSPORT NOTES	Not Classified
RAIL TRANSPORT NOTES	Not Classified.
SEA TRANSPORT NOTES	Not Classified.
AIR TRANSPORT NOTES	Not Classified.

SECTION 15 REGULATORY INFORMATION

RISK PHRASES NC Not classified. SAFETY PHRASES NC Not classified.

SECTION 16 OTHER INFORMATION

NOTES: National Fire Protection Association standards NFPA 654 and 68 indicate possible explosion hazard of dust particles. Conform accordingly. Avoid accumulation of dust or dust clouds; operate handling and storage systems leak free, practice good housekeeping. Keep from sources of ignition. Do not store near heat, flame, or strong oxidants. Assure proper electrical grounding of all handling equipment.

Product may also contain varying levels of additives, such as slip and no blocking agents, antioxidants, stabilizers, and corrosion inhibitors. Certain grades may contain talcum, as an additive that is encapsulated in the polymer. Inhaled talcum in an occupational environment has been not classified as a Group 1 human carcinogen by the International Agency for Research on Cancer. Centerplastics limited Company has assessed the potential for release of talcum to the air when this polymer is handled and has determined that talcum encapsulated in this polymer







DATE: MARCH 2011

MATERIAL SAFETY DATA SHEET

is not expected to pose a health hazard when processed under normal conditions of use.

REVISION SUMMARY: March 2011 **REVISION N.1**

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATE-RIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE, AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILIVTY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER WARRANTY AGAINST PATENT INFRINGEMENT.